

Product Specification, Surface, Low Flow SF5000C



SF5000C

GENERAL DESIGN FEATURES

- The Original Pressure Independent Rate Control with over 30 years of successful field history.
- Pressure Independent Flow Regulation Constant flow regardless of pressure fluctuations
- No scheduled maintenance
- Ceramic trim for maximum reliability

PRESSURE BALANCED PISTON

- Pressure Independence Upstream and downstream pressure fluctuations create a net force on the patented pressure balanced piston, which is countered by a spring force to maintain constant flow.
- Stable and Accurate Flow Delivery Pressure balanced piston provides instantaneous means of control at different injection points from a common line that is more tolerant to debris and fluid filming. No pneumatic or electric power sources required for control.
- Debris Management Accumulated debris result in a net force on the piston that instantaneously lifts the pin slightly from the seat, passing debris through the outlet. This net force is countered by the spring force that returns the piston to its balanced flow rate position.

SKOFLO BENEFITS

- ★ 30-year experience, industry expert and solution provider
- Pressure Independent Valve Technology (PIVT)
- Significant chemical OPEX cost savings



Product Specification, Surface, Low Flow SF5000C

DESIGN RATINGS

Turndown Ratio	10:1		
Minimum Differential Pressure	200 psi (14 bar) required to regulate flow independent of pressure.		
Working Pressure Rating	5,000 psig (345 barg)		
Proof Test Pressure	7,500 psig (517 barg)		
Operating Temperature	FFKM	FKM	EPDM
Operating Temperature Rating	-20°F to 185°F	-50°F to 185°F	-50°F to 185°F
	(-29°C to 85°C)	(-45°C to 85°C)	(-45°C to 85°C)
Storage Temperature Rating	-50°F to 185°F (-45°C to 85°C)		
Viscosity	0.5 – 100 cP		
Debris Tolerance	SAE AS4059 Class 12B-F		
Installation Orientation	Horizontal or Vertical		
Envelope Dimensions	8in. x Ø4in. (230mm x Ø127 mm)		
Weight	9 lb. (4.1 Kg)		
Process Connections	¼" NPT Female		

MATERIALS - CHEMICALLY WETTED

Valve Body	316 SS	
Metallic Components	316/316L SS	
Non-metallic Components	PTFE, FFKM, FKM, EPDM, Alumina, Zirconia	
Valve Trim	Ceramic	

 SPEC-11686 Rev B
 www.SkoFlo.com
 Main Line: (425) 485-7816